





Durability

Weather and pollution resistant

Easy installation & maintenance

Flexibility

Cost effective

Fast track construction solution with characters

Flexibility & versatility

Strong and unbreakable

Environmental friendly

Recyclable material

Fire retardant

Providing extra safety







Our team of skilled experts are dedicated to the "Quality First" philosophy we work to attain, which has led to our products being recognized for the innovative and high-quality materials in the market.











Art Elegance Unique





Wide range of choices



CNC cutting compatible



Weather friendly



Easy maintenance



Heat resistant



Flexible



Impact resistant



UV resistant



Lightweight



Sound resistant



Even surface



Long lasting



Environment friendly



Easy installation



Termite resistant



Solvent resistant



Protective coating




Scratch resistant



NOTE: ORDER BASED ON SEALED SAMPLE

The colours on this chart are just for reference and only for polyester. A slide colour variation may occur between products such as PVDF coating and polyester coating. For exact colour matching, please request for actual colour sample. Colour variations may occur between panels originating from different production batchers. To ensure colour consistency, the total project should be placed in one order.

Panel Composition



Product specifications

Technical Data

3Bond ACP Dimensions		
Item	Specification	
Standard width	1220mm	
Standard length	2440mm (8ft)	
	3660mm (12ft)	
	4270mm (14ft)	
	4880mm (16ft)	
	5490mm (18ft)	
	6100mm (20ft)	
Available thickness	4mm	

Product Comparison Chart

Item	3Bond (ACP)	Polycarbonate	Steel
Weight	4mm: 4.2kg/m2	4.5mm: 5.328kg/m2	1.5mm: 11.78kg/m2
Heat insulation	Good	Poor	Poor
Sound insulation	Good	Poor	Poor
Flatness	Good	Normal	Poor
Echo response	Low	Low	High
Colour consistency	High	High	Low
Fireproof	Good	Poor	Good
Weatherproof	Good	Poor	Good
Paint thickness	Even	(-)	Uneven
Installation	Fast	Normal	Slow
Maintenance	Easy	Difficult	Easy
Cost	Economy	Normal	Normal
Delivery	Fast	Fast	Slow
Fabrication	Easy	Easy	Difficult



